



DESIGN

1. SINKS.
 - A. SINKS SHALL BE ON FLOOR.
 - B. KNEE CLEARANCE SHALL BE PROVIDED.
 - C. SINKS SHALL BE PROVIDED WITH WATER SUPPLY OR OTHERWISE SHARP OR ABRASIVE.
 - D. A CLEAR FLOOR PROVIDED IN FRONT OF SINKS SHALL BE A MAXIMUM OF 18" HIGH.
2. DOORS.
 - A. DOOR HARDWARE SHALL BE GRASP WITH ONE HAND AND TWISTING OF THE WRIST SHALL BE NO MORE THAN 15°.
3. DINING / WORK SURFACES.
 - A. THE TOP OF THE SURFACE SHALL BE MINIMUM WORK CLEARANCE LONG FOR FREQUENT USE UNDER THE WORK SURFACE.
 - B. FLOOR SURFACE SHALL BE STEEPER THAN 1:12.
4. SALES AND SERVICE COUNTERS.
 - A. PARALLEL APPROACH.
 - 1) A PORTION OF THE COUNTER SHALL BE PARALLEL TO THE APPROACH.
 - 2) WHERE THE COUNTER IS PERPENDICULAR TO THE APPROACH, A CLEARANCE OF 48" SHALL BE PROVIDED.
 - B. FORWARD APPROACH.
 - 1) A PORTION OF THE COUNTER SHALL BE PARALLEL TO THE APPROACH.
 - 2) A CLEARANCE OF 48" SHALL BE PROVIDED.
 - 3) KNEE SPACE SHALL BE PROVIDED UNDER THE COUNTER.
5. SIGNAGE.
 - A. SIGNAGE SHALL BE PROVIDED AT THE FOLLOWING LOCATIONS:
 - 1) AT EACH ENTRANCE.
 - 2) SIGNAGE SHALL BE PROVIDED TO IDENTIFY THE UNIT.
 - 3) SIGNAGE SHALL BE PROVIDED TO IDENTIFY THE UNIT.
 - 4) SIGNAGE SHALL BE PROVIDED TO IDENTIFY THE UNIT.
 - B. ALL SIGNAGE SHALL BE PROVIDED IN A CLEAR AND LEGIBLE MANNER.
 - C. SIGNAGE SHALL BE PROVIDED TO IDENTIFY THE UNIT.
 - D. SIGNAGE SHALL BE PROVIDED TO IDENTIFY THE UNIT.

